

# url

## Description

Core\Uri **url()**

Using our **url()** function will give you access to our core url class, which is used to handle primarily the creation of links and sending users from one page to another.

## Examples

```
<?php

// Create a URL
echo url()->make('/foo'); // Converts to http://localhost/foo

// Sends a user to another route
url()->send('/foo');
```

## Methods

| Method  | Description                 | Usage   | Returns        |
|---|-----------------------------|---|----------------|
| <b>make</b> (string \$route [, array \$params = [] ] )<br><br><a href="#">\$route</a><br>URL route.<br><br><a href="#">\$params</a><br>(optional) Params can be passed, which will be converted into GET requests.  | Creates a new link.         | <pre>// Create a URL echo url()-&gt;make('/foo'); // Converts to http://localhost/foo  // Create a URL echo url()-&gt;make('/foo', ['hello' =&gt; 'world']); // Converts to http://localhost/foo?hello=world</pre>  | Prepared link. |
| <b>send</b> (string \$route [, array \$params = [], string \$message = null])<br><br><a href="#">\$route</a><br>Provide the segment number of the URL.<br><br><a href="#">\$params</a><br>(optional) Params can be passed, which will be converted into GET requests.<br><br><a href="#">\$message</a><br>(optional) Message to display to the user once they have reached the next page. | Sends the user to the link. | <pre>// Sends a user to another route url()-&gt;send('/foo');  // Sends a user to another route with GET params url()-&gt;send('/foo', ['hello' =&gt; 'world']);  // Send a user to another route with a message url()-&gt;send('/foo', ['hello' =&gt; 'world'], 'Successfully Updated!');  // Send a user to another route with a message and without additional GET params url()-&gt;send('/foo', 'Successfully Updated!');</pre> | null           |