Manage Settings

App Settings

Site Settings

Adding

On function setSettings in Install.php add following code

Which:

- array_key and var_name: They should be the same. In this case, we use: td_can_user_privacy. It's unique var_name that you can call this
 setting. Moreover, you should use you own app's prefix (like "td", stands for "to do") for your settings in order not to conflict with other settings.
- · info: Short information about this setting.
- · description: Full information about this setting.
- type: Type of this setting.
- value: Default value of this setting

For now (4.5.*), we supported follow type of setting

- radio
- text
- select
- password

You can check you setting by go to AdminCP -> App -> TodoList (this app) -> Settings



Using

We use function **setting** to get value of a setting

```
<?php
$value = setting('td_can_user_privacy');</pre>
```

User Group Settings

Adding

On function setUserGroupSettings in Install.php add following code

```
<?php
public function setUserGroupSettings()
   $this->user_group_settings = [
        'td_can_add_new_todo_list'
           'var_name' => 'td_can_add_new_todo_list',
           'info' => 'Can add new todo list?',
                    => \Core\App\Install\Setting\Groups::TYPE_RADIO,
           'value' => [
               "1" => "1",
               "2" => "1",
               "3" => "1",
               "4" => "1",
               "5" => "0"
           ],
            'options' => \Core\App\Install\Setting\Groups::$OPTION_YES_NO
       ],
   ];
}
```

Which:

- array_key and var_name: They should be the same. In this case, we use: td_can_add_new_todo_list. It's a unique var_name that you can call
 this user group setting. (View above settings' naming rule)
- info: Description for your user group setting
- type: Type of this user group setting.
- value: Default value of this user group setting per each user group (user group ID)

For now (4.5.*), we supported follow type of user group setting

- radio
- text
- currency

User Group ID note:

- 1: Administrator
- 2: Registered User
- 3: Guest
- 4: Staff
- 5: Banned

Apps » TodoList » User Group Settings » Registered User (ID#2)

User Group Settings » Registered User (ID#2)



Using

We use function **user** to get value of a user group setting

```
<?php
$value = user('td_can_add_new_todo_list');</pre>
```

Next Chapter